

FILTER CHAMBERS

Discs or Cartridges

Series 3 - PP

up to 6000 l/h
100 l/min

The series has a robust, compact and reliable construction. This results in maximum installation uptime and a long service life, providing best in class performance, technically and economically. The series is designed and manufactured for filtration of chemical solutions, service friendly with ideal cleaning access height.

Features

- Filter chamber with welded bottom (no seal)
- Machined from Simona® AlphaPlus™ high performance PP
- Top plate made of glass-filled PP
- Including complete +GF+ union ends
- EPDM elastomers
- Discs (thin/thick paper, cloth) or cartridges
- Max. temperature PP 80°C
- Stainless steel fittings, fasteners and type shields
- Pressure gauge and air release



F-31A-K-PP

Options

- Customised mounting plate
- Hose connections
- In-Tank version (IT)
- 30" version (33A)
- Union sockets in PVC or CPVC
- Specific elastomers
- Contact pressure gauge
- Single open end cartridges
- PP legs (standard 300 mm)
- Fittings and fasteners in titanium or electroless nickel coated

F	Medium	Material	In	Out
	K/P	PP-EPDM	d25/DN20	

Selection example: F-31A-K-PP

K = cartridges

Qty x L
31A-K = 3 x 10"
32A-K = 3 x 20"

P = discs

Qty	OD/ID	m²
31A-P = 32	136/32	0,4
32A-P = 65	136/32	0,9

standard maximum pressure				
°C	°F	Mpa	bar	psi
20	68	0,35	3,5	50
55	131	0,35	3,5	50
80	176	0,25	2,5	36

T +31 497 339 389
info@hendor.com

WWW.HENDOR.COM