

## Harlequin Storage Tank



Stock No	<a href="#">TR037</a>
Model	2500BFS/A BioFuel Station
Other Info	Storage and dispensing of Diesel oil
Location	Our Central Warehouse, Aldridge, UK
Weight (kgs)	200 kg
External Dimensions (WxDxH mm)	Ø2090 x 1930 mm

### Description

2500BFS/A BioFuel Station

Bunded plastic BioDiesel storage and dispensing tank, rotationally moulded from a premium, specialist grade of BioDiesel resistant Medium Density Polyethylene and supplied complete with:

- \* 2" Fill Point with Screw Cap
- \* 4" Inspection Point with Screw Cap
- \* Vent
- \* Apollo Electronic Oil Tank Contents Gauge
- \* Bund Warning Alarm
- \* LRC Failsafe Overfill Prevention Capability
- \* Lockable Access

The Marketplace for Surface Technology.  
New and Used Process Equipment & Machinery.  
**Machine Datasheet**



- \* 240v Electric Pump
- \* 10 micron Fuel Filtration System
- \* 4 metre Fuel Delivery Hose with Automatic Shut Off Nozzle
- \* Mechanical Flow Meter with Resettable Batch Totaliser
- \* Emergency Isolation Switch
- \* Bulkhead Light

#### Applications

Suitable for the storage and dispensing of Diesel and BioDiesel grades up to B100, produced in accordance with the requirements of BS/IS EN14214 – including national Summer and Winter Fuel requirements for CFPP(1) in the UK and Republic of Ireland - at agricultural, commercial, industrial and institutional premises.

Satisfies or exceeds all applicable product requirements detailed within:

- \* The Control of Pollution (Oil Storage) (England) Regulations 2001
- \* The Control of Pollution (Silage, Slurry and Agricultural Fuel Oil) Regulations 1991
- \* The Control of Pollution (Silage, Slurry and Agricultural Fuel Oil) Regulations (Northern Ireland) 2003
- \* The Water Environment (Oil Storage) (Scotland) Regulations 2006
- \* Environmental Alliance Pollution Prevention Guidelines PPG 2

(1) CFPP is the Cold Filter Plug Point which indicates the temperature at or below which a fuel may begin to cause operational problems. British Standard BS EN14214 and Irish Standard IS EN14214 states Summer and Winter requirements within the UK and Republic of Ireland as -5 degrees Celsius and -15 degrees Celsius respectively.

#### Details:

Diameter: 2090 mm

Height: 1930 mm

Weight: 200 kg

Actual Capacity: 2716 litres

Nominal Capacity: 2580 litres

List price new £4492.50

**Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.**