

Nederman Spark Arrestor Box



Stock No	EU1420C
Manufacturer	Nederman
Model	Spark trap box
Approx Duty CFM / M ³ /Hr	3500 // 6000
Filter Area ft ² / m ²	N/A
Other Info	350mm Dia Inlet/Outlet
Location	Our Central Warehouse, Aldridge, UK
External Dimensions (WxDxH mm)	820 x 820 x 1130

Description

Nederman In-line spark traps reduce the possibility of fire by knocking down sparks from the airstream before they can enter your dust collection unit.

The dust laden air enters the spark trap and expands reducing the velocity and allowing the heavier particles to separate.

The air is then directed downwards by a deflection plate and impinged upon a bed of water contained within the catchment tray.

This helps extinguish the sparks before the air passes through to the secondary chamber and on to your extraction source.

The Marketplace for Surface Technology.
New and Used Process Equipment & Machinery.
Machine Datasheet



The collection bin is then emptied at regular periods and the water within replenished.

Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.



Surface
Engineering
Association

Riley Industries Ltd
A subsidiary of Barry Riley & Sons Ltd. Director: M P A Riley, Secretary: D Hemming
Registered in England no. 1965748



European
Association of
Machine Tool
Merchants