The Marketplace for Surface Technology. New and Used Process Equipment & Machinery.

Machine Datasheet



B O Morris Morrisflex Non stop Model 401 Polishing Lathe



Stock No Manufacturer

Model Condition R.P.M.

Hp/Kw Other Info Location

Weight (kgs)

External Dimensions (WxDxH mm)

PE1209 B O Morris

None Stop 401 + Drive lock & Duel Speed From a working environment, Good Condition

1500 : 3000 2 x 3hp (2.2kW)

Independent End, Duel Speed Model Our Central Warehouse, Aldridge, UK

250

1400 x 750 x 1250

Description

The Morrisflex Model 401 is a heavy duty independently controlled double sided pedestal mounted polishing machine that is equipped with 4 heavy duty bearings for smooth running and a long service life.

This traditionally built heavy duty second hand Morrisflex model 401 Polishing lathe is predominately used with polishing mops, buffs and bobs, but can also be used with a wide range of rotary abrasive tools, ie abrasive impregnated nylon wheels, abrasive brushes, flap wheels, deburring wheels, and wire wheels etc.

The body of the machine is manufactured from cast aluminium keeping the weight down and offering excellent heat





The Marketplace for Surface Technology. New and Used Process Equipment & Machinery.

Machine Datasheet



dissipation. The installed twin spindles are powered by robust high torque motors offering speeds of 2800 per end, making them suitable for a wide range of applications and materials.

Benefits

4 bearing design guarantees long life and vibration free running greatly reducing the risk of vibration related industrial conditions such as white finger.

Independent ends reduce power consumption whilst being used by a single operator and allow two operators to work simultaneously and independently of each other.

Features and Specifications

- Motor sizes: 3hp 2.2KW per motor
- Heavy duty 4 bearing spindles
- Contact wheel/buff diameters: 250 mm with taper spindle ends or 350 mm with parallel ends

Optional Extras

- Parallel or tapered spindles ends
- Variable speed motor drives
- Dust extractor
- Dust collection hoods
- Back stand idlers / linishing and belt grinding attachments

Dual Ended independent start polishing lathe

SUPPLY = 400/440Volt, 3 phase, 50 Hz

Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.



