

Plymovent Draftmax Ultra Bench



Stock No	EE2262
Manufacturer	Plymovent
Model	DraftMax Ultra
Serial	D0361310014
Condition	From a working environment, Good Condition, Current Model
Approx Duty CFM / M ³ /Hr	1500CFM // 2500M ³ /Hr
Filter Area ft ² / m ²	560ft ² // 52M ²
Other Info	Pulse Jet Filter Cleaning
Location	Our Central Warehouse, Aldridge, UK
Weight (kgs)	255
External Dimensions (WxDxH mm)	1380 x 1005 x (920mm to 970mm)

Description

DOWNDRAFT TABLE WITH AUTOMATIC SELF-CLEANING FILTER + BACK DRAFT KIT + SIDE PANELS

- The DraftMax Ultra is a workbench that provides extraction and filtration for welding and grinding applications. The DraftMax Ultra features a work grid, a three-stage pre filtration system for optimum spark arresting and two self cleaning main filter cartridges. Both pre and main filters have pull-out dust drawers underneath. The filter cleaning system starts when the pressure drop reaches a certain maximum value during use (online cleaning). The filter



cartridges are individually cleaned from the inside by compressed air shots. An integrated buzzer indicates when the filter cartridges need to be replaced. For welding and grinding applications the DraftMax Ultra must be fitted with a backdraft kit for optimum division of the extraction capacity (approx. 80% backdraft, 20% downdraft). Filter exchange and service (except for the membrane valves) can be effected from the front side.

Applications

The DraftMax Ultra is intended to be used for the following applications:

All below require the correct accessories to be used;

- MIG-MAG/GMAW welding¹
- TIG welding¹
- FCAW welding
- Stick/MMAW welding
- Grinding
- Cutting (max. 50 A)

Specifications

- 2.2kW 3Hp Motor.
- 3 Stage spark arresters : 1st Below work grid. : 2nd Labyrinth spark trap. : 3rd Spark arrester in main filter housing.
- Simple control.
- Option to add Hepa filters.

Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.