

Vibromak 75kg Centrifugal Dryer



Stock No	NEW170
Manufacturer	Vibromak
Model	VKSK 75
Capacity	40 Litres : 75kg Max Load
Type	Centrifugal Drying
Other Info	Stainless Steel Basket : Brake Motor
Weight (kgs)	240
External Dimensions (WxDxH mm)	860 x 1200 x 1700mm (Lid Open)

Description

A brand-new centrifugal parts dryer designed for fast, efficient drying - featuring a perforated basket within a 525 rev/min rotating drum and a powerful lid-mounted fan that circulates hot air through the load for rapid, even results. Most appropriate for small parts being processed in bulk.

Due to the close proximity of the parts and resistance they offer to free air flow, these applications often present challenges to normal convection dryers.

Centrifugal Drying


Overcomes those obstacles and speeds up production by drying two ways. Centrifugal force from the spinning action of

The Marketplace for Surface Technology.
New and Used Process Equipment & Machinery.
Machine Datasheet



the basket "throws off" excess water, oils, or other liquids. At the same time, a turbine fan mounted below the basket creates a powerful suction that pulls air through the parts load for added drying power. This double-drying action assures fast drying and reduces the scarring and marring frequently responsible for costly rejects. In most cases, producing spot-free, moisture-free parts in under 60 seconds.

**Spin Speed of
525 rev/min
Fast Drying**



**Stainless
Steel Basket
Durable Design**



**Rear Fitted
Brake Motor
Quickly Stop to
Reduce Wear**



**Safety Switch
Automatically
Stop Process
When Opened**



**Seperate Control Panel
Includes Easy to Set
Timer & Timer Controls**

Specification

- External dimensions (lid open) - 860mm x 1200mm x 1700mm
- Spin speed - 525 rev/min with brake motor
- Approx. basket size - 500mm x 375mm
- Working capacity - 40 Litres



Surface
Engineering
Association

Riley Industries Ltd
A subsidiary of Barry Riley & Sons Ltd. Director: M P A Riley, Secretary: D Hemming
Registered in England no. 1965748



European
Association of
Machine Tool
Merchants



- Weight capacity - 75kg
- Motor - 3Hp // 2.2kW
- Fan heater - 2000 Watts
- Stainless steel basket
- Lid safety switch
- Digital process timer

Optional Hoist

Images 22 and 23 show an optional manual hoist which is available. This hoist is manually operated and is only suitable for use with lighter loads as there is no locking mechanism.

Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.