

Wadkin Bursgreen PLC CP Panel Table Saw



Stock No	ME933
Manufacturer	Wadkin Bursgreen PLC
Model	CP12 Panel Table Saw
Serial	85164
Condition	From a working environment, Good Condition
Capacity	Blades Ø400 x 3.2 Bore Ø25mm
Process Application	Wood / Composites Cutting
Other Info	Ideal for cutting Flat Sheets / Boards
Location	Our Central Warehouse, Aldridge, UK
External Dimensions (WxDxH mm)	2500 x 2400 x 900mm

Description

A powerful machine with sliding table, canting arbor and scoring saw. Of sound robust construction, incorporating a comprehensive range of standard features usually considered as extras. Highly versatile with a wide range of applications. The CP12 combines the heavy duty features of the large Wadkin Bursgreen CP25 machine with the sliding table of the very popular SP12 machine. For a small capital investment the machine will soon prove to be a valuable asset to any workshop, large or small.

- Any of the CP Range will perform a wide variety of functions with consummate ease and provide the perfect finish.

Cross-cut, mitre and rip fences have gradated, scales with micro adjustment for absolute precision and speed of operation. The sliding table glides effortlessly on specially developed runners which also give maximum support. Operator comfort is further ensured with ergonomically convenient controls and positive adjustments ensuring ease of operation.

- With a precision ground fixed table and wider sliding table than any other similar sized machine, it's not surprising that the CP Range is so popular. The five models in the range offer complete flexibility not only in the size of panel capable of being processed but also materials. These heavy duty canting table saws are capable of cutting panels, boards, solid timber, plastics and "soft" metals - all with the same accuracy and efficiency

Spec.

- CP12 1200 mm - SLIDING TABLE PANEL SAW (WITH SCORING) - Rise, fall and tilt saw, fixed table 1065 x 737 mm (42" x 29"), sliding table 1350 x 1300 mm (53" x 51"), fitted with cross cut fence with stop bar and two stops. 4 kW (5.5 HP) (3 phase). Capacity: Takes sawblades 400 mm (16") dia and cuts 125 mm (5") deep, saw to rip fence (max) 1250 mm (50"), max distance in front of saw when cutting 25 mm (1") deep is 1250 mm (50") and distance from saw to stops on sliding table is 2500 mm (98").

Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.