

## Metalas MC125 Top Loading Spray Wash



Stock No	<a href="#">DF1618J</a>
Manufacturer	<a href="#">Metalas</a>
Model	MC125
Year of Manufacture	2008Ref 26
Serial	982948/08
Condition	Refurbished by RSW, Good Condition
Work Envelope (WxDxH mm)	Ø1200mm Basket
Process Stages	Single Stage Wash System
Other Info	Max. Grid Load 500Kg's
Location	Our Central Warehouse, Aldridge, UK
Weight (kgs)	350
External Dimensions (WxDxH mm)	1450 x 1570 x 1135mm (Lid up 2260mm)

### Description

These Metalas MC 125 cleaning machines are specially designed for cleaning components in industrial and maintenance workshops during both manufacture and assembly, requiring less space to achieve maximum cleaning efficiency with minimum operating costs.

Metalas rotary spray cleaners put a stop to all other time consuming and high cost cleaning methods. cleaning machines are specially designed for cleaning components in industrial and maintenance workshops during both manufacture and



assembly, as well as refurbishing in the motor vehicle trade and all at minimal cost.

The surprisingly effective and thorough cleaning is obtained by the combination of high velocity spray jets, a large volume of heated detergent water and bouncing whirlpool action which cleans the dirtiest parts in 5 to 15 minutes and all within a totally enclosed system.

The machine can clean everything, not only ferrous and non ferrous metals but also plastics etc.

### Standard Features:

- Magnetic lid locking
- Wash timer 0-60 mins
- Temperature controlled thermostat 0-120°C
- Heating Switch
- Heating pilot light
- Lid protection switch
- Covered liquid tank
- Continuous return flow filtration
- Filter
- Drain valve 2" BSP
- Immersion heater
- Switch control panel box fitted with mains isolator
- Thermal motor overload protection

### Specification

- Dimension (WxDxH) - 1450mm x 1570mm x 1135mm
- Height (lid open) - 2260mm
- Loading surface (round) - Ø120mm
- Useful height - 550mm
- 415 Volt , 3 phase, 50 Hz
- Admissible grid load 500kg
- Temp range 0 -100°C
- Capacity pump/motor 18 m<sup>3</sup>hr / 2.2kw
- Pressure 2.2 Bar
- Liquid contents 100 litre
- Electric heating 9kW (2 off 4.5kW heating elements)
- Lid protection switch

**Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.**