

Rosler RM620 Finishing Bowl



Stock No	VF2556
Manufacturer	Rosler
Model	RM620
Year of Manufacture	2000
Serial	28117/00
Condition	From a working environment, Excellent Condition
Capacity	620Litres
Type	Vibratory Bowl
Other Info	Available as a Cell with 4 bowls & Dryer
Location	Our Central Warehouse, Aldridge, UK
External Dimensions (WxDxH mm)	Ø1700mm x 1200mm Tall

Description

Rösler R Series rotary vibrators feature a flat bottom work bowl designed to process large, bulky and delicate components with excellent workpiece immersion and controlled movement. Bottom unloading allows the bowl to be fully emptied, with media and components separated externally. The system is supplied with a control panel and dosing unit for straightforward process management.

The flat bottom design provides excellent embedding of components within the media, while optional fan dividers allow particularly delicate parts to be processed separately, reducing unwanted contact and impact.

Vibratory Finishing Process

Vibratory finishing uses a work bowl mounted on coil springs, with a central vibratory motor generating the movement required to create friction between the components and finishing media. Continuous water and compound dosing supports the process, helping achieve consistent finishing results.

Applications

Highly versatile, rotary vibrators can perform a wide range of finishing operations, including:

- Deburring and grinding
- Radiusing and edge rounding
- Cleaning and descaling
- Degreasing and polishing
- Processing of stamped, cast, formed, forged, sawn and machined components

Suitable for metals, plastics, ceramics, rubber, wood, stone and glass, vibratory finishing can be used for everything from small, delicate components to large and robust workpieces.

Flexible Processing Options

The bulk-discharge design supports three main processing methods:

1. Part-on-Part Processing

Components can be processed without media for applications such as deburring stampings or part-on-part burnishing and polishing. Once complete, parts can be quickly removed through the unload gate.

2. Large & Delicate Components

The flat-bottom bowl allows larger or sensitive components to be processed with reduced part-to-part impact. Components move in a controlled spiral around the bowl and rise towards the surface, allowing easy manual removal without a separation screen.

3. Intricate Components & Post-Treatment

For applications where media separation is required, parts and media can be discharged together through an extended separation screen. This helps remove media from trapped holes and allows additional processes such as washing and drying, while also enabling undersized media to be removed to maintain optimum processing performance.

Technical Details

- Flat bottom processing channel (i.e. No exit ramp)
- Rösler double flange dual speed vibratory motor 1500 rpm / 1000 rpm process speed at 50 Hz; easy and safe lubrication of the bearings
- Adjustable imbalance weights allow different grinding intensities
- Wear resistant lining made from hot poured polyurethane
- Media, parts unload plug with integrated effluent drain



- Flexible design of control panels and compound dosing systems

Process bowl Specification

- Total volume - 620 Litres
- External diameter max. - 1700mm
- Process bowl width - 430mm
- Average overall length of processing channel - 4000mm
- Machine height - 1200mm
- Height media unload plug- 625mm
- Drive power connected load - 4.5 / 7.5kW

Control Panel

- Treatment timer
- Self start delay timer
- Run hours meter
- Dosing pump control
- Forward and reverse vibrator direction selector switch
- Isolator switch

Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.